

CETPATCH FH 2917

Non-metallic non-oxidizing floor hardener

DESCRIPTION

CETPATCH FH are supplied as a ready to use factory controlled cementitious system blended with special aggregates selected for high abrasion and wear resistance and additives. Based on non-metallic non oxidizing aggregate used to produce an impact and wear resistant, dust free surface suitable for most heavy-duty area.

FEATURES :

- Highly impact and abrasion resistance.
- Long lasting wear resistant surface.
- Dry shake on applied over fresh concrete to provide a monolithic bond.
- Resists oil and grease penetration and reduces dusting.
- Non slip and anti-skid.

AREAS OF APPLICATION :

- Engineering work-shops.
- Where houses.
- Production areas.
- Garages
- Subways
- Railway platforms.
- Loading bays.
- Ship yards & Utility building.

MIXING

Ready to use sprinkle directly on green concrete.

COVERAGE

4.7kg - 5kg to 2-3.5mm



SHELF LIFE : 12 months.

PACKING : 40kg

APPLICATION PROCESS

- Apply 30 mm thick cement layer.
- Sprinkle dry FH during initial set.
- Sprinkle 2nd layer once material is dark.

PHYSICAL PROPERTIES

Testing Parameter	Test Method	FH 2917
MOH'S Scale	Internal	7-8
Compressive strength	Internal	>50/nm
VOC content	Internal	4.53g/l